

XBee-PRO PKG™ RF Modems

ZigBee™/IEEE® 802.15.4 Stand-alone Radio Modems by MaxStream, Inc.

XBee-PRO PKG™ RF Modems

Indoor/urban Range:	up to 300' (100 m)
Outdoor line-of-sight Range:	up to 1 mile (1.6 km)
Transmit Power Output:	100 mW (20 dBm) EIRP
Operating Frequency:	2.4 GHz
RF Data Rate:	250,000 bps
Receiver Sensitivity:	-100 dBm

Interfaces Available



***XBee-PRO PKG-R™
RS-232***



***XBee-PRO PKG-U™
USB***



***All the benefits of the ZigBee & 802.15.4 protocols
wrapped into to one easy-to-use RF modem***

Easy-to-Use! No configuration is necessary for out-of-box RF operation. Simply feed data into one modem, then the data is sent out the other end of the wireless link. If more advanced functionality is needed, the modems support an extensive set of AT commands.

Key Features



Price-to-Performance Value.

Due to innovations stamped in its design, the XBee-PRO yields 2-3x the range of standard ZigBee modems. This allows OEMs & integrators to cover more ground with fewer devices.

Additionally, XBee-PRO Modems are easy-to-use and therefore greatly reduce the cost of data system development.



Receiver Sensitivity.

MaxStream Modems 'hear' what others cannot; therefore supplying greater range and reliability in wireless links.

For every 6 dB gained in TX power or RX sensitivity, OEMs and integrators can double the range of a wireless link. XBee-PRO modems outperform higher costing modems due in large part to range gained through superior RX sensitivity.



Transmit Power Output.

The XBee-PRO outputs 100 mW (20 dBm) EIRP while consuming only 300 mA current (5V power supply).



Worldwide Acceptance.

FCC (U.S.A.), IC (Canada), ETSI (Europe) pending



Systems that contain XBee-PRO Modems inherit MaxStream's certifications. Contact MaxStream for a complete list of government agency approvals.

Sample Applications

**Security systems
& lighting controls**



**Home automation
& building control**



**Home appliances
& fire/CO2 alarms**



**Monitoring of
remote systems**



**Sensor data capture
in embedded networks**



Call today!

- Free RF Consultation
- Volume Discounts
- Development Kit Pricing



MaxStream®

(866) 765-9885 toll-free in U.S. & Canada

(801) 765-9885 worldwide

www.maxstream.net

XBee-PRO PKG™ 2.4 GHz RF Modems

Specifications		XBee-PRO PKG-R™ (RS-232)	XBee-PRO PKG-U™ (USB)
Performance	Indoor/Urban Range (w/ 2.1 dB dipole antenna)	up to 300 ft. (100 m)	
	Outdoor RF line-of-sight Range (w/ 2.1 dB dipole antenna)	up to 1 mile (1.6 km)	
	Transmit Power Output	60 mW (18 dBm), 100 mW (20 dBm) EIRP	
	Receiver Sensitivity	-100 dBm (1% PER (Packet Error Rate))	
	Interface Data Rate (software selectable)	1200 - 115200 bps (non-standard baud rates also supported)	
	RF Data Rate	250,000 bps	
Networking & Security	Frequency Range	ISM 2.4 GHz	
	Spread Spectrum	DSSS (Direct Sequence Spread Spectrum)	
	Modulation	OQPSK (Offset Quadrature Phase Shift Keying)	
	Supported Network Topologies	Peer-to-peer (no master/slave dependencies), Point-to-point, Point-to-multipoint & Mesh (coming soon)	
	Number of channels (software selectable)	13 Direct Sequence Channels	
	Filtration Options	PAN ID, Channel & Destination/Source Addresses	
Antenna	Connector Options	RPSMA (reverse polarity SMA)	
	Impedance	50 ohms unbalanced	
Certifications (partial list)	FCC Part 15.247	pending	
	Industry Canada (IC)	pending	
		XBee-PRO PKG-R™	XBee-PRO PKG-U™
Power Requirements	Power Supply Voltage	5 - 14 VDC	USB bus power
	Transmit Current	300 mA (@ 9V) *	300 mA **
	Receive Current	80 mA	90 mA
	Power Down Current	< 6 mA	< 25 mA
Physical Properties	Size	4.500" x 2.750" x 1.125" (11.4cm x 7.0cm x 2.9cm)	
	Weight	5.25 oz (150 g)	
	Data Connection	female DB-9	USB
	Operating Temperature	-40 to 85° C (Industrial)	0 to 70° C (Commercial)

* Average current while streaming data (@9600 bps) = 86 mA

** Average current while streaming data (@9600 bps) = 92 mA

Specifications are subject to change without notice.



**For the best in wireless data solutions and support,
contact MaxStream, Inc.**

phone: (866) 765-9885 (toll-free in U.S. & Canada)
(801) 765-9885 (worldwide)

fax: (801) 765-9895

web: www.maxstream.net
(live chat & many other resources available)



MaxStream®

355 South, 520 West, ste. 180
Lindon, UT 84042

© 2005 MaxStream, Inc.